BALL VALVES



MIC Ball valves are widely used in

All types of Instruments, Control panels and pilot plants,

Refineries, Process plants, Laboratories and Power Plants,

Hydraulic and Pneumatic piping,

The field of Chromatography, Steam generation and food processing,

High-pressure Hydraulic systems and Equipments.


Many other areas of instrumentation and research.

DESIGN FEATURES

- 1. Pressure up to 5000psi (345bar).
- 2. Temperature from 65° F (19.5 C) to 450° F (232 C).
- 3. Free floating ball allows pressure actuation in closed position.
- 4. Rugged construction for long life.
- 5. Quick 1/4 turn actuation.
- 6. Highest level of leak free integrity.
- 7. Full material traceability.
- 8. Choice of different handles.
- 9. Available with choice of Pneumatic and electric actuators.

BALL VALVES

1




STANDARD BALL VALVE

			MATERIAL OF CONSTRUCTION		
NO.	DESCRIPTION	QTY	STAINLESS STEEL	CARBON STEEL	
1	Body	1	SS	CS	
2	Ball	1	SS	SS	
3	Side Piece	1	SS	CS	
4	Seat	2	PTFE/DELRIN	PTFE/DELRIN	
5	Gasket/O-Ring	1	PTFE/VITON A	PTFE/VITON A	
6	Stem packing	2	PTFE/DELRIN	PTFE/DELRIN	
7	Stem	1	SS	SS	
8	Gland Packing	1	PTFE/DELRIN	PTFE/DELRIN	
9	Gland	1	SS	SS	
10	Spring Washer	1	SS	CS	
11	Gland Nut	1	SS	CS	
12	Handle	1	SS	CS	
13	Lock Pin	1	SS	CS	
14	Handle Nut	1	SS	CS	

STANDARD BALL VALVE

MIC	ORIFICE		CONNECTION SIZE	DIMENSIONS			5
NUMBER	in	mm	INLET/OUTLET	A	В	HOPEN	L
1IBVST8TT8T	0.411	10.4	1/2 Tube	3.94	1.97		
1BVST12T12T	0.411	10.4	12 MM Tube	3.94	1.97		
2IBVST8F8F	0.516	13.1	1/2 Female NPT	3.12	1.56		
2IBVST12F12F	0.516	13.1	3/4 Tube			2.34	4.38
3IBVST12F12F	0.875	22.2	3/4 Female NPT	4.24 2.12			
3BVST16F16F	0.875	22.2	1 Female NPT				
3IBVST16T16T	0.875	22.2	1 Tube			i I	

2



HIGH PRESSURE BALL VALVE

			MATERIAL OF CONSTRUCTION		
NO.	DESCRIPTION	QTY	STAINLESS STEEL	CARBON STEEL	
1	Body	1	SS	CS	
2	Ball	1	SS	SS	
3	Side Piece	2	SS	CS	
4	Seat	2	PTFE/DELRIN	PTFE/DELRIN	
5	Gasket/O-Ring	2	PTFE/VITON A	PTFE/VITON A	
6	Stem packing	2	PTFE/DELRIN	PTFE/DELRIN	
7	Stem	1	SS	SS	
8	Gland Packing	1	PTFE/DELRIN	PTFE/DELRIN	
9	Gland	1	SS	SS	
10	Spring Washer	1	SS	CS	
11	Gland Nut	1	SS	CS	
12	Handle	1	SS	CS	
13	Lock Pin	1	SS	CS	
14	Handle Nut	1	SS	CS	
15	End Coupling	2	SS	CS	